Patent/Publication

Number

453056

Title Adaptive power control in a radio communications system

Issued/Publication

Date

2001/09/01

2000/03/15 **Application Date**

089104717 **Application Number**

Certification Number 140105

ipc **H04B-007/00**(2006.01);

(IPC 1-7): H04B-007/00

MULLER, WALTER SE; Inventor

RIMHAGEN, THOMAS SE;

BARK, GUNNAR SE

TELEFONAKTIEBOLAGET LM ERICSSON SE Applicant

Priority Number 19990315 US 19990267686

Abstract Delays on a common radio communications channel employed by

> plural mobile stations to communicate with a base station located in a corresponding geographical cell area are minimized by adapting transmission power based on traffic conditions. For lower traffic loads, a higher transmission power is permitted. For higher traffic loads, a lower power level is set. A transmit power level is determined using a desired signal ratio, such as a target CIR, a transmission path loss over the radio communications channel, and an interference value. One or

more adaptive power parameters are also employed in that determination to adapt the open loop power control based on one or more current communications conditions and/or characteristics of the mobile station. For example, an adaptive power parameter may be a function of a current interference in a base station cell either alone or in combination with a current interference in one or more neighboring cells. The adaptive power parameter may also account for a type of data packet connection to be employed between the mobile station and the base station after random access, a mobile station^s subscription, a current temperature of the mobile station, a current base station used by the mobile station, a current estimated path loss

between the mobile station and base station, and/or other factors.